

EC1621 Electronic clock instructions manual v01

Because the product features more, please read this manual carefully, thank you for your cooperation!

Function introduction:

Digital tube display: On the electric silence that time, temperature, year, month, day, week round display, through the button can be set to display only time or display the time and temperature (in the "time display settings").

Time Setting: Can be set time by key .

Speech time: set the speech time in Chinese or English.

Hourly Chime: Can be open or closed, can set the time period by button (for example, can be set to 8 in the morning to 22 o'clock in the evening time, the other time is not hourly chime).

Alarm: There are 4 alarm clock, can be turned off or on, can be set the length of alarm time and alarm rings.

The first alarm clock for ordinary, when opened will be alarm every day.

The second alarm clock for the workday, when open every Monday to Friday alarm, Saturday and Sunday no alarm.

The Third alarm clock for the weekend, when open Saturday and Sunday alarm, Monday to Friday no alarm.

The fourth is a single alarm clock, when open only alarm one times.

Ring: output music with speakers.Can change their own ring, can be set to alarm bells.

Temperature Display: Measuring ambient temperature with thermistor.The default is the degree Celsius display, can be set by the key to Fahrenheit display.When the temperature is not allowed to do when the temperature calibration (in the "temperature calibration settings") (for example: when the display temperature is 3 degrees higher than the actual temperature, the temperature calibration value can be set to -3).

Light Control: Measurement of ambient brightness with photosensitive resistors.When the ambient light becomes dark, it will automatically reduce the brightness of the clock. Can set the dark state clock brightness.

12/24 hour system: The default is 24 hours, can be set by the button for the display of 12 hours (in the "12/24 hours set mode").

Stopwatch: the shortest time is 0.01 seconds, the longest time 2 days.

Countdown: the length of the 2 day countdown, countdown to the end of the bell.And can set the countdown time and countdown to the end of the bell.

Some errors in welding:

- 1、Clock chip (DS3231) no welding or welding error. Show "Eor1".
- 2、Thermistor (temperature measurement circuit) no welding or welding error. Show "Eor2".
- 3、Photosensitive resistor (metering circuit) without welding or welding error. Show "Eor3".

Electrical performance:

Power supply: DC3V~DC5V

Working current: <40mA

Alarm current: <70mA

Electronic clock display and key function

Time display:

	Display description	MODE key function in mode	PLUS key function in mode
Time display mode (power on default mode)	There are 3 display modes: 1, time, temperature, year, month, day, week round display. 2, time, temperature wheel display. 3, only display time.	1, short press, enter the time setting mode. 2, long press 3 seconds into the hourly chime and alarm settings. 3, Long press 5 seconds to enter the function settings.	1, fixed time display mode, the first round of temperature, year, month, day, week. 2, Hold down the MODE key and then press the PLUS key to enter stopwatch and countdown mode.

Time Setting:

It can modify the time of the clock, in each setting if more than 10 seconds without any key press, then automatically returns the time display, and restore the time before.

Mode	Display description	PLUS key function in mode	MODE key function in mode
Time display mode			Short press enter (year set mode)
Year Set Mode	Four digital tube flashing shows "Year"	Set "Year", long press can quickly set	Into next mode (Month set mode)
Month Set Mode	front two tube flashing shows "Month", after two tube always shows "Day"	Set "Month", long press can quickly set	Into next mode (Day set mode)
Day Set Mode	Front two tube always shows "Month", after two tube flashing shows "Day"	Set "Day", long press can quickly set	Into next mode (Hour set mode)
Hour Set Mode	Front two tube flashing shows "Hour", after two tube always shows "H" when 24 hour system, when 12 hour system shows "A" in am, shows "P" in pm.	Set "Hour", long press can quickly set	Into next mode (Minute set mode)
Minute Set Mode	Front two tube always shows "Hour", after two tube flashing shows "Minute"	Set "Minute", long press can quickly set	Into next mode (Second set mode)
Second set mode	Front two tube always shows " — — ", after two tube flashing shows "Second"	Set "Second", long press can quickly set	If there is a time to adjust, save the settings, otherwise not save the settings, and return time display mode.

Hourly Chime and Alarm Setting:

It can be set hourly Chime and 4 alarm clocks, each setting mode, press the MODE button for 3 seconds or 10 seconds without any button is pressed, will automatically return time display mode.

Mode	Display description	PLUS key function in mode	MODE key function in mode
Time Display Mode			Press the MODE button 3 seconds to enter (the hourly chime switch mode)

Hourly Chime Switch Mode	Front two tube always shows "01", after two tube flashing shows "On" or "OF" to express open or close the hourly chime	Open or close the hourly chime	Into next mode (Hourly Chime Star Time Mode)
Hourly Chime Star Time Mode	Front two tube always shows "02", after two tube flashing shows hourly chime star time	Set star time(for example: the start time is set to 8, the end time is set to 22, the day of 8 o'clock to 22 o'clock will be hourly chime)	Into next mode (Hourly Chime End Time Mode)
Hourly Chime End Time Mode	Front two tube always shows "03", after two tube flashing shows hourly chime end time	Set end time(for example: the start time is set to 8, the end time is set to 22, the day of 8 o'clock to 22 o'clock will be hourly chime)	Into next mode (Time Chinese or English settings)
Time Chinese or English Set Mode	Front two tube always shows "04", after two tube flashing shows "ON" or "OF" express English or Chinese to tell the time.	English or Chinese to tell the time.	Into next mode (Alarm clock 1 switch setting mode)
Alarm clock 1 switch setting mode	Front two tube always shows "05", after two tube flashing shows "ON" or "OF" express open or close the alarm clock 1	Open or close alarm clock 1	Into next mode (the hour set for alarm clock 1 mode)
Hour Set For Alarm Clock 1	Front two tube always shows "06", after two tube flashing shows the hour of alarm 1	Set the hour of alarm 1,long press can quickly set	Into next mode (the minute set for alarm clock 1 mode)
Minute Set For Alarm Clock 1	Front two tube always shows "07", after two tube flashing shows the minute of alarm 1	Set the minute of alarm 1,long press can quickly set	Into next mode (the alarm time length set for alarm clock 1)
Alarm Time Length Set For Alarm Clock 1	Front two tube always shows "08", after two tube flashing shows the alarm time length of alarm 1	Set the alarm time length of alarm 1,Set range of 1 ~ 20 minutes	Into next mode (the rings set for alarm clock 1)
Rings Set For Alarm clock 1	Front two tube always shows "09", after two tube flashing shows the serial number of the rings for alarm 2	Set alarm 1 rings (have 12 rings)	Into next mode (Alarm clock 2 switch setting mode)
Alarm clock2 switch setting mode	Front two tube always shows "10", after two tube flashing shows "ON" or "OF" express open or close the alarm clock 2	Open or close alarm clock 2	Into next mode (the hour set for alarm clock 2 mode)
Hour Set For Alarm Clock 2	Front two tube always shows "11", after two tube flashing shows the hour of alarm 2	Set the hour of alarm 2,long press can quickly set	Into next mode (the minute set for alarm clock 2 mode)
Minute Set For Alarm Clock 2	Front two tube always shows "12", after two tube flashing shows the minute of alarm 2	Set the minute of alarm 2,long press can quickly set	Into next mode (the alarm time length set for alarm clock 2)
Alarm Time Length Set For Alarm Clock 2	Front two tube always shows "13", after two tube flashing shows the alarm time length of	Set the alarm time length of alarm 2,Set range of 1 ~ 20 minutes	Into next mode (the rings set for alarm clock 2)

	alarm 2		
Rings Set For Alarm clock 2	Front two tube always shows “14”, after two tube flashing shows the serial number of the rings for alarm 2	Set alarm 2 rings (have 12 rings)	Into next mode (Alarm clock 3 switch setting mode)
Alarm clock 3 switch setting mode	Front two tube always shows “15”, after two tube flashing shows “ON” or “OF” express open or close the alarm clock 3	Open or close alarm clock 3	Into next mode (the hour set for alarm clock 3 mode)
Hour Set For Alarm Clock 3	Front two tube always shows “16”, after two tube flashing shows the hour of alarm 3	Set the hour of alarm 3, long press can quickly set	Into next mode (the minute set for alarm clock 3 mode)
Minute Set For Alarm Clock 3	Front two tube always shows “17”, after two tube flashing shows the minute of alarm 3	Set the minute of alarm 3, long press can quickly set	Into next mode (the alarm time length set for alarm clock 3)
Alarm Time Length Set For Alarm Clock 3	Front two tube always shows “18”, after two tube flashing shows the alarm time length of alarm 3	Set the alarm time length of alarm 3, Set range of 1 ~ 20 minutes	Into next mode (the rings set for alarm clock 3)
Rings Set For Alarm clock 3	Front two tube always shows “19”, after two tube flashing shows the serial number of the rings for alarm 4	Set alarm 3 rings (have 12 rings)	Into next mode (Alarm clock 4 switch setting mode)
Alarm clock 4 switch setting mode	Front two tube always shows “20”, after two tube flashing shows “ON” or “OF” express open or close the alarm clock 4	Open or close alarm clock 4	Into next mode (the hour set for alarm clock 4 mode)
Hour Set For Alarm Clock 4	Front two tube always shows “21”, after two tube flashing shows the hour of alarm 4	Set the hour of alarm 4, long press can quickly set	Into next mode (the minute set for alarm clock 4 mode)
Minute Set For Alarm Clock 4	Front two tube always shows “22”, after two tube flashing shows the minute of alarm 4	Set the minute of alarm 4, long press can quickly set	Into next mode (the alarm time length set for alarm clock 4)
Alarm Time Length Set For Alarm Clock 4	Front two tube always shows “23”, after two tube flashing shows the alarm time length of alarm 4	Set the alarm time length of alarm 4, Set range of 1 ~ 20 minutes	Into next mode (the rings set for alarm clock 4)
Rings Set For Alarm clock 4	Front two tube always shows “24”, after two tube flashing shows the serial number of the rings for alarm 4	Set alarm 4 rings (have 12 rings)	return time display mode.

Function Setting:

each setting mode, press the MODE button for 3 seconds or 10 seconds without any button is pressed, will automatically return time display mode.

Mode	Display description	PLUS key function in mode	MODE key function in mode
Time Display Mode			Press the MODE button above 5 seconds to enter (light control switch mode)
Light Control Switch mode	The first tube always shows “1 ”, after two tube flashing shows “ON” or “OF” express open or close the light control	open or close the light control	Into next mode (the light control level settings)
Dark Brightness Settings	The first tube always shows “2 ”, after two tube flashing shows the Brightness	Set Brightness (There are -2, -1, 0, 1, 2 a total of 5 grades)	Into next mode (Fahrenheit temperature display switch settings)
Fahrenheit Temperature Display Switch Settings	The first tube always shows “3 ”, after two tube flashing shows “ON” or “OF” express Fahrenheit or Centigrade display	Set Fahrenheit or Centigrade display	Into next mode (temperature calibration setting mode)
Temperature Calibration Setting Mode	The first tube always shows “4 ”, after two tube flashing shows temperature calibration value	Set temperature calibration value, Range from -9 to 10.(For example, when the display temperature is 3 degrees higher than the actual temperature, the calibration value can be set to -3).	Into next mode (12/24 hour display setting mode)
12/24 Hour Display Setting Mode	The first tube always shows “5 ”, after two tube flashing shows “ON” or “OF” express 12 hour or 24 hour display	Set 12/24 hour display	Into next mode (time display setting mode)
Time Display Setting Mode	The first tube always shows “6 ”, after two tube flashing shows round display mode	Set round display mode (have 3 kinds),0: only display time. 1: time, temperature, year, month, day, week round display. 3: time and temperature round display.	Into next mode (volume setting mode)
Volume Setting Mode	The first tube always shows “1 ”, after two tube flashing shows volume value	Set volume	return time display mode.

Stopwatch and countdown:

Mode	Display description	PLUS key function in mode	MODE key function in mode
Time Display Mode		Hold down the MODE key, then press the PLUS button, enter (stopwatch)	
stopwatch	stopwatch	Short press can start or pause time, long press 3 seconds or more to start the countdown.	Into next mode (countdown hour set)
countdown hour set	Front two tube always shows “1 —”, after two tube flashing shows the countdown hour	Set the value of the countdown hour	Into next mode (countdown minute set)
countdown minute set	Front two tube always shows “2 —”, after two tube flashing shows the countdown minute	Set the value of the countdown minute	Into next mode (countdown second set)
countdown second set	Front two tube always shows “3 —”, after two tube flashing shows the countdown second	Set the value of the countdown second	Into next mode (Countdown end ring set)
Countdown end ring set	Front two tube always shows “4 —”, after two tube flashing shows the Countdown end of the bell number	Set the countdown to the end of the ring	Into next mode (Countdown)
Countdown	Countdown		return time display mode.